

GOSANA

FLOOR PAINT



Gosana is a water-based emulsion composed of acrylic polymers and selected ingredients. It is specially formulated to be used as floor paint, as an alternate for applying cow dung on the floor, at the entrance of buildings.

PRODUCT CHARACTERISTICS

PROPERTIES	SPECIFICATIONS
Nature	Smooth paste
Colour	Cow dung colour
Specific gravity @ 27°C	1.40 ± 0.05
Non-volatile content	55.00 ± 5.00%
Viscosity	3000 – 5000 cP
pH	8.00 ± 1.00
Finish	Rich matt
Surface dry	30 minutes
Over coating interval	4 – 6 hours
Stability of thinned paint	24 hours

USES

Concrete flooring

| Artificial and natural stones.

BENEFITS

Rich matt finish | Good hiding property | Abrasion resistance | Waterproofing & does not fade with weather | Very good intercoat adhesion | Can be applied by brush or rollers or spray | Free from heavy metals like mercury, lead and chromium.

SHELF LIFE & STORAGE

Best before 12 months in an unopened,

undamaged, originally sealed packing and if stored in dry conditions

| Protect from direct sunlight.

RECOMMENDED DOSAGE

400 ml of water per litre of cement primer.

COVERAGE

60 – 70 sq.ft/ litre/ coat .

DIRECTIONS OF USE

Floor must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting | Application should start 4 hours after the application of Primer

| Dilute with 40% of water by volume

to Gosana and stir thoroughly to get

homogenous mixture | Apply single coat

and allow it to dry for about 2-4 hours

| After 2-4 hours, apply another coat.

NOTE

Ambient and surface temperatures must

be between 5°C and 40°C during application

| The moisture content of the wall must

be less than 10% or have aged for at least 28 days.

HEALTH & SAFETY PRECAUTIONS

Use rubber hand gloves & safety

goggles | In case of contact with skin,

wash with plenty of water

| Keep out of reach of children.

PACKAGING

1 Lt



4 Lt



10 Lt



20 Lt

