
## **REVE FIX**

## TILE FIXING ADHESIVE



Reve Fix is a polymer modified, cement-based, pre-packed and ready to use tile adhesive.

PACKAGING

PRODUCT CHARACTERISTICS	
PROPERTIES	SPECIFICATIONS
Appearance	Grey colour
	lump free powder
Open time	15 - 20 minutes
Tapped	
density	1.80 - 2.10
Pot Life	60 minutes
USES	

Fixing all types tiles on internal and external walls/floors | Tiling applications in swimming pools.
BENEFITS

Ready to use, needs only mixing of water I Excellent adhesion and slip resistance | Excellent waterproofing | Crack free and low shrinkage | No need for presoaking of tiles and water curing | Suitable for both interior and exterior applications Better open time. **SHELF LIFE & STORAGE** Best before 12 months in an unopened, undamaged, originally sealed packing and if stored in dry conditions Protect from direct sunlight. **RECOMMENDED DOSAGE** 300 ml water per kg of Reve Fix powder. COVERAGE 4 sq.ft / kg for 3 mm thickness.

**DIRECTIONS OF USE** 

The surface to be tiled must be clean and dry I Existing tiles should be clean and securely fixed I Add 1 kg of Reve Fix powder to 300 ml potable water I Mix thoroughly until a smooth creamy consistency is obtained I Allow the mixture to stand for 10 minutes I Mix again and start applying with a trowel I Apply a thin bed of 3 mm thickness by a trowel. Comb the surface gently and start placing tiles before the adhesive begins to surface dry I While fixing the tiles into the adhesive apply slight pressure to ensure good adhesion. NOTE

Do not apply directly on damp surfaces I Do not use to fix heavy tiles or stones, marble, granite, etc on vertical areas I Grouting should not be done for at least 24 hours. **HEALTH & SAFETY PRECAUTIONS** Use rubber hand gloves & safety goggles I In case of contact with skin, wash with plenty of water I Keep out of reach of children. **CLEANING OF TOOLS** Clean all tools and application equipments with water immediately after use.

I Cured material can be removed mechanically.