

# TILE PLUS

A PLEASANT PAINT FOR ROOF TILES



Tile Plus is a specially designed pleasant paint for Kollam and Mangaluru clay roofing tiles.

It is composed of advanced polymer ingredients and is a water-soluble environmental friendly product.

## PACKAGING

1 Lt



4 Lt



10 Lt



20 Lt



## PRODUCT CHARACTERISTICS

PROPERTIES	SPECIFICATIONS
Type	Solvent based
Colour	As per customer requirement
Specific gravity @ 27°C	1.00 ± 0.05
Non-volatile content	40.00 ± 5.00%
Viscosity	100 - 200 cP
Finish	Rich Matt
Touch dry	1 hour
Hard dry	8 hours
Over coating interval	4 – 6 hours

## USES

Kollam and Mangaluru clay roofing tiles  
| Exterior brick works.

## BENEFITS

Rich matt finish | Good hiding property  
| Allows the surface to breathe and expel moisture | Colour never faded | Algae and fungal resistance | Waterproofing  
| Free from heavy metals like mercury, lead and chromium.

## SHELF LIFE & STORAGE

Best before 12 months in an unopened, undamaged, originally sealed packing and if stored in dry conditions  
| Protect from direct sunlight.

## RECOMMENDED DOSAGE

400 ml of water per litre of cement primer.

## COVERAGE

80 – 90 sq.ft / litre / coat.

## DIRECTIONS OF USE

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting | Dampen the surface with water | Dilute with 40% of water by volume to Tile Plus and stir thoroughly to get a homogenous mixture  
| Apply single coat and allow it to dry for about 2-4 hours with brush / rollers  
| After 4 – 6 hours, apply another coat  
| Two coats are recommended.

## NOTE

Ambient and surface temperatures must be between 5°C and 40°C during application  
| The moisture content of the wall must be less than 10% or have aged for at least 28 days.

## HEALTH & SAFETY PRECAUTIONS

Use rubber hand gloves & safety goggles | In case of contact with skin, wash with plenty of water  
| Keep out of reach of children.

## CLEANING OF TOOLS

Clean all tools and application equipments with proper thinner or kerosene immediately after use.