

# V - FLEX G2K

## ACRYLIC CEMENTITIOUS WATER-PROOFING COATING



V-Flex G2K is a two-component cementitious polymer modified elastomeric, waterproofing & protective coating, which reduces the room temperature up to 7 – 9°C at peak summer hours.

### PRODUCT CHARACTERISTICS

PROPERTIES	SPECIFICATIONS
Nature	Two-component
Appearance of mix	Free-flowing slurry
Specific gravity @ 27°C	1.60±0.10
Viscosity of mix	10000 ± 2000 cP
pH	10.00 – 12.00
Pot life of mix	40 – 45 minutes
Surface dry	30 minutes
Water permeability after coating interval	Excellent – no leakage after 24 hours 4 – 6 hours

### USES

Concrete walls, roofs, terrace | Concrete roof slabs, floors, balcony floor slabs | Water tanks and swimming pools | Waterproof coating (bottom coat) for marble, granite and other natural stones.

### BENEFITS

Flexible and permeable coating | Waterproofing for concrete structures | Excellent adhesion to concrete and natural stones | Can be applied as thick coating.

### RECOMMENDED MIX RATIO

4:1 (Part A: Part B)  
(Part A = Powder & Part B = Liquid).

### SHELF LIFE & STORAGE

Best before 12 months in an unopened, undamaged, originally sealed packing and if stored in dry conditions

| Protect from direct sunlight.

### COVERAGE

70 – 80 sq.ft/litre/coat.

### DIRECTIONS OF USE

All surfaces must be clean, dry and free of dirt, chalk, grease, oil, wax, rust and loose or peeling paint before painting | Repair holes and cracks with a thick paste of V-Flex G2K prepared in the recommended ratio

| Prepare the main batch of V-Flex G2K in the recommended ratio and stir thoroughly to get a homogenous mixture

| Wet the surface with water by sprinkler and apply single coat and allow it to dry for about 2-4 hours

| After 2-4 hours, repeat the above process.

### NOTE

The entire quantity of both the components have to be mixed and used at one go

| For best results do not dilution with water.

### HEALTH & SAFETY PRECAUTIONS

Use rubber hand gloves & safety goggles

| In case of contact with skin, wash with plenty of water

| Keep out of reach of children.

### PACKAGING

