

# VECO PRIMER

CEM PRIMER  
WATER THINNABLE



Veco Cement Primer is a water-based acrylic primer suitable for interior & exterior sand plastered surfaces, concrete and asbestos, etc.

## PRODUCT CHARACTERISTICS

PROPERTIES	SPECIFICATIONS
Nature	White, smooth paste
Viscosity	10000 ± 2000 cP
Specific gravity @ 27°C	1.50±0.05
Non-volatile content	50 – 60%
pH	10.00 ± 1.00
Sheen level	Soft sheen
Surface dry	30 minutes
Over coating interval	4 – 6 hours
Stability of thinned paint	24 hours

## USES

Cement plasters, concrete, cementitious renderings | Asbestos, brick works, gypsum boards | False ceilings.

## BENEFITS

Smooth finish | Good hiding power | Allows the surface to breathe and expel moisture | Seals porous surfaces | Very good intercoat adhesion | Seals chalky surfaces, improves top coat adhesion | Free from heavy metals like mercury, lead and chromium.

## SHELF LIFE & STORAGE

Best before 12 months in an unopened,

undamaged, originally sealed packing and if stored in dry conditions

| Protect from direct sunlight.

## RECOMMENDED DILUTION

750 ml of water per litre of cement primer.

## COVERAGE

110 – 120 sq.ft/litre/coat.

## DIRECTIONS OF USE

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting

| Repair holes and cracks with suitable filler | Dilute with 75% of water by volume to get a homogenous mixture

| Apply single coat and allow it to dry for about 2-4 hours.

## NOTE

Ambient and surface temperatures must be between 5°C and 40°C during application | The moisture content of the wall must be less than 10% or have aged for at least 28 days.

## HEALTH & SAFETY PRECAUTIONS

Use rubber hand gloves & safety goggles | In case of contact with skin, wash with plenty of water

| Keep out of reach of children.

## PACKAGING

