

VECO DISTEMPER

ACRYLIC EMULSION BASED DISTEMPER



Veco Distemper is a water-based emulsion composed of acrylic polymers and special ingredients.

PRODUCT CHARACTERISTICS

PROPERTIES	SPECIFICATIONS
Nature	Smooth paste
Viscosity	25000 ± 5000 cP
Specific gravity @ 27°C	1.50±0.05
Non-volatile content	60±5%
pH	8.00 – 10.00
Finish	Rich matt
Surface dry	30 minutes
Colour	Base / White
Over coating interval	4 – 6 hours
Stability of thinned paint	24 hours

USES

Decorative coating for interior walls & plastered surfaces | Decorative coating for dry wall surfaces like gypsum, cement fibre boards, etc.

BENEFITS

Rich matt finish | Good hiding property | Allows the surface to breathe and expel moisture | Waterproofing | Can be applied by brush or rollers | Available in both Base and White variants | Base can be tinted with different colours.

SHELF LIFE & STORAGE

Best before 12 months in an unopened, undamaged, originally sealed packing and if stored in dry conditions | Protect from direct sunlight.

RECOMMENDED DILUTION

600 ml of water per kg of distemper.

COVERAGE

80 – 90 sq.ft / litre / coat.

DIRECTIONS OF USE

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting | Application should start after 4 hours from the application of Veco Cement Primer | Dilute with 40% of water by volume to Veco Distemper and stir thoroughly to get a homogenous mixture | Apply single coat and allow it to dry for about 2-4 hours | After 2-4 hours, apply another coat.

NOTE

Ambient and surface temperatures must be between 5°C and 40°C during application | The moisture content of the wall must be less than 10% or have aged for at least 28 days.

HEALTH & SAFETY PRECAUTIONS

Use rubber hand gloves & safety goggles | In case of contact with skin, wash with plenty of water | Keep out of reach of children.

PACKAGING

