

VIJAY ULTIMA

SMOOTH FINISH
EXTERIOR EMULSION



Vijay Ultima is a water-based emulsion composed of acrylic polymers and special ingredients.

PRODUCT CHARACTERISTICS

PROPERTIES	SPECIFICATIONS
Nature	Smooth paste
Colour	As per customer requirement
Specific gravity @ 27°C	1.10±0.05
Non-volatile content	45.00±5.00%
Viscosity	15000 ± 2000 cP
pH	8.00 ± 1.00
Finish	Rich matt
Surface dry	30 minutes
Over coating interval	4 – 6 hours
Stability of thinned paint	24 hours

USES

Decorative coating for exterior walls & plastered surfaces | Exterior coating for dry wall surfaces like gypsum, cement fibre boards, asbestos sheets etc.

BENEFITS

Rich matt finish | Good hiding property | Allows the surface to breathe and expel moisture | Waterproofing | Very good intercoat adhesion | Can be applied by brush or rollers | Free from heavy metals like mercury, lead and chromium.

SHELF LIFE & STORAGE

Best before 12 months in an unopened, undamaged, originally sealed packing and if stored in dry conditions
| Protect from direct sunlight.

RECOMMENDED DOSAGE

400 ml of water per litre of cement primer.

COVERAGE

120 – 140 sq.ft/litre/coat.

DIRECTIONS OF USE

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting
| Application should start 4 hours after the application of Primer | Dilute with 40% of water by volume to Vijay Ultima and stir thoroughly to get a homogenous mixture | Apply single coat and allow it to dry for about 4-6 hours | After 2-4 hours, apply another coat.

NOTE

The moisture content of the wall must be less than 10% or have aged for at least 28 days
| Ambient and surface temperatures must be between 5°C and 40°C during application.

HEALTH & SAFETY PRECAUTIONS

Use rubber hand gloves & safety goggles | In case of contact with skin, wash with plenty of water
| Keep out of reach of children.

PACKAGING

1 Lt



4 Lt



10 Lt



20 Lt

