

VIJAY WHITE

WALL CARE PUTTY



Vijay White Wall Care Putty is a specially formulated powder putty with unique raw materials & additives.

PRODUCT CHARACTERISTICS

PROPERTIES	SPECIFICATIONS
Appearance	White lump-free powder
Drying time	Initial = 40 – 60 min Final = 4 – 6 hours
Pot Life of thinned material	1 – 1.5 hours
Tensile adhesion	> 1.0 N/mm ² after 28 days
Water retentivity	> 98%
Tapped density	1.5 – 1.7 g/cc
Recoatability	2 – 3 hours

USES

Interior & Exterior plastered surfaces
| concrete, rendered wall, hollow block, precast walls, concrete ceilings, aerated light-weight blocks.

BENEFITS

Excellent whiteness & smooth finish
| Excellent workability and ease of application | Prevents water leakage
| Prevents growth of algae and fungus
| Provides ideal base for painting | Never peels off | Provides good breathability
| Anti-flaking | No blistering
| No chalking | No curing required.

SHELF LIFE & STORAGE

Best before 12 months in an unopened, undamaged, originally sealed packing and if stored in dry conditions | Protect from direct sunlight.

Recommended Dilution

1st coat = 40% v/w depending on surface conditions
2nd coat = 45 - 50% v/w depending on surface conditions

PACKAGING



COVERAGE

2 sq.mtr / kg / 2 coats on well prepared substrate.

DIRECTIONS OF USE

Clean the surface with emery paper, putty blade or wire brush. Moisten the wall with clean water. There should be no dirt, oil traces or algae on the surface | Mix the putty with 40 % water by volume to Vijay White to prepare a uniform paste. Add the water gradually. Stir the mix thoroughly to avoid formation of lumps. Let it rest for 10 minutes. Give the paste a good mix once more | Apply first coat of putty starting from the bottom of the wall in an upward direction uniformly using a putty knife | Allow it to dry for 2 -3 hours and then rib the surface gently with fine emery paper to remove loose particles
| Apply the second coat with fresh material and maintain the total thickness of the two coats to about 1.5 mm
| Allow it to dry for at least 10 – 12 hours.

NOTE

Not recommended for painted or non-cementitious surfaces
| Ensure the material is mixed homogenously with water
| Once the putty paste is hardened, it should not be softened by the addition of water and applied on the wall.

HEALTH & SAFETY PRECAUTIONS

Use rubber hand gloves & safety goggles
| In case of contact with skin, wash with plenty of water
| Keep out of reach of children.